

Self-Declaration

30th March 2022

Experience a safer
and more open world

Testing Summary

Summary of test and extended application evidence, designed to facilitate the interchangeability of building hardware for application to fire resisting and/or smoke control doorsets and/or openable windows tested to EN1634

| DC200 | Timber | | | | Steel | | | | |
|---------------|--------|-----|-----|------|-------|-----|-----|------|------|
| | 30m | 60m | 90m | 120m | 30m | 60m | 90m | 120m | 240m |
| Test report | | | | | | | | | |
| WF196799 AR | X | X | X | X | | | | | |
| UL 4788943227 | | | | | X | X | X | X | X |

Hardware identification

Manufacturer: ASSA ABLOY EMEA DC PU, Shenfei, China

Product reference: D200 EN 2-4 door closer

| EN 1154:1996+A1:2002 | | | | | |
|----------------------|---|-----|---|---|---|
| 4 | 8 | 2-4 | 1 | 1 | 4 |

CE number: 2812-CPR-AD5247

Test info

Fitted with or without satin stainless-steel cover fitted in

- Pull side door mounted
- Push side door mounted
- Push side transom mounted

Having a fire doorset performance of up to and including 240 minutes
Uninsulated Steel Doorsets & Insulated Steel Doorsets.
Fireside and Non-fire side suitable.

Timber Doorsets up to and including 120-minutes and that both substrates are fire and non-fire side compliant.



Name
Title

