

Eclipse Size 2-4 Overhead Door Closer



Technical Information

- CE 1121, UKCA 2812, CF6145Certifire
- BS EN1154 Performance Tested
- Adjustable by Template 3-4 Door Closer
- Tested to 500,000 Opening Cycles
- BS EN1634 Fire Tested
- FD 30, 60, 90, 120 Minute Timber
- FIG 1 - Pull Side (180° Maximum Opening)
- FIG 61 - Transom (170° Maximum Opening)
- FIG 66 - Push Side (170° Maximum Opening)
- Tested to Operating Temperatures of -15°C to 40°C
- 10 Year Mechanical Guarantee
- Parallel Arm Bracket Supplied
- Adjustable Closing
- Adjustable Latching

| Ref | Pack Contents | Qty | Finish |
|-------|-----------------------|-------|--------|
| 28831 | Unit, Arm, PA Bracket | 1 Set | SLV |
| 28832 | Unit, Arm, PA Bracket | 1 Set | WE |
| 28833 | Unit, Arm, PA Bracket | 1 Set | BLK |
| 28835 | Complete with Cover | 1 Set | SLV |
| 28837 | Complete with Cover | 1 Set | BLK |
| 28838 | Complete with Cover | 1 Set | PCP |
| 28839 | Complete with Cover | 1 Set | SNP |
| 28836 | Complete with Cover | 1 Set | PBP |
| 28840 | Complete With Cover | 1 Set | SBP |
| 28841 | Complete With Cover | 1 Set | MAB |
| 28842 | Complete With Cover | 1 Set | DBZ |

FIG 1

| | | | | | |
|---|---|-----|---|---|---|
| 4 | 8 | 3/4 | 1 | 1 | 3 |
|---|---|-----|---|---|---|

FIG 66 & FIG 61

| | | | | | |
|---|---|---|---|---|---|
| 3 | 8 | 3 | 1 | 1 | 3 |
|---|---|---|---|---|---|